



# VISTA VPT

## RANGE OF PAN AND TILT HEADS



### IDEAL FOR APPLICATIONS SUCH AS:

Virtually any external installation, especially:

- Town centres
- Large office blocks
- Government & military installations
- Industrial sites

### MAIN FEATURES:

- AC & DC power options
- Preset options
- IP66
- 25Kg max load



### INSTALLER FRIENDLY PAN AND TILT HEADS

The Vista Protos range of Pan & Tilts have been thoughtfully designed to look stylish and be easy to install. Each unit is based on a top mount pan and tilt which is rated to IP66, finished in a polyester powder coat and coloured RAL7035.

The VPT range has unique side handles for ease of positioning and a hook for attaching a safety chain, ensuring they meet the very latest safety standards.

The VPT range is available in a selection of voltages and autopan is available as an option.



## THE UK'S PREMIER CCTV BRAND



## TECHNICAL SPECIFICATIONS

	VPT25K240(p)	VPTDC
MAXIMUM LOAD	25Kg	
PAN MOVEMENT	5° to 350°	
TILT MOVEMENT	12° to -90°	
PAN SPEED	7.5°/s	48°/s
TILT SPEED	3°/s	16°/s
TORQUE	150Kg/cm Pan / 400Kg/cm Tilt	
BACK LASH	0.5°	
PRESETS	Optional (VPT25K240P)	Standard
AUTOPAN	Optional (VPT25K240A)	No
POWER	240V AC	24V DC
POWER CONSUMPTION	24VA	36VA
WEIGHT	7.5Kg	
OPERATING TEMP	-20° ~ +55°C	
FINISH	Polyester Powder Coated to RAL7035	
ENVIRONMENTAL PROTECTION	BS.EN.60529 Level IP66	

## ORDERING INFORMATION

VPT25K240	25KG LOAD, EXTERNAL PAN & TILT UNIT, 240V AC
VPT25K240P	25KG LOAD, EXTERNAL PAN & TILT UNIT, 240V AC, PRESETS
VPT25K240A	25KG LOAD, EXTERNAL PAN & TILT UNIT, 240V AC, AUTOPAN
VPTDC	25KG LOAD, EXTERNAL PAN & TILT UNIT, 24V DC, PRESETS

DISTRIBUTED BY:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



**VISTA** NORBAIN HOUSE, ESKDALE ROAD, WINNERSH TRIANGLE, WOKINGHAM, BERKSHIRE. RG41 5TS  
 TELEPHONE: +44 (0) 118 944 0123 FAX: +44 (0) 118 944 0999  
 WEBSITE: WWW.VISTA-CCTV.COM